



TotalEnergies

# Classic 5 SF SAE 40

## KEY DATA



Classic  
5

**LIGHT VEHICLE RANGE**

**INTERNATIONAL STANDARDS**

🔥 API SF/(CD)

<sup>1</sup> Please refer to car owner's manual

## **CLASSIC, THE GUARANTEED QUALITY**

Multigrade oil for all gasoline and Diesel, formulation using a set of additives with carefully selected performance and proportions to answer to the quality standards of the Association of the European Manufacturers (ACEA).

## **APPLICATIONS**

Recommended for Petrol and Diesel engines in cars and light vans.

Permits use at all temperature and any type of service : city, highway, mountain, rough road ....

## **CUSTOMERS BENEFITS**

- 🔥 Detergent-dispersant capability keeping engine components clean.
- 🔥 Thermal stability and oxidation resistance.
- 🔥 Anti-wear properties.

## CHARACTERISTICS<sup>2</sup>

TEST	UNIT	RESULT
Viscosity grade	-	SAE 40
Kinematic viscosity at 40°C	mm <sup>2</sup> /s	130
Kinematic viscosity at 100°C	mm <sup>2</sup> /s	13.5
Density at 15°C	kg/m <sup>3</sup>	898
Viscosity index	-	98
Pour point	°C	-12
OC Flash point	°C	242

<sup>2</sup> The characteristics given above are obtained with a standard tolerance threshold during production and may not be considered specifications.

## RECOMMENDATIONS FOR USE

Before using the product, the vehicle's maintenance guide should be checked. Oil changes should be carried out in accordance with the manufacturer's recommendations.

The product should not be stored at temperatures over 60°C. It should be kept away from sunlight, intense cold and extreme temperature fluctuations. If possible, the packaging should not be exposed to the elements. Otherwise, the drums should be laid horizontally in order to avoid any contamination from water and to prevent the product's label from rubbing off.

## HEALTH, SAFETY AND THE ENVIRONMENT

Based on the toxicological information available, this product should not cause any adverse health effects, provided it is used for its intended purpose and in accordance with the recommendations laid out in the Safety Data Sheet (SDS).

This can be obtained on request from your local reseller and is available for consultation at <https://ms-sds.totalenergies.com>.

This product should not be used for any purposes other than the ones for which it is intended.

